

FLAM'UP CHIMNEY LOG

UVC – CASE

Characteristics: Log composed of sawdust and hardwood shavings (Mainly from untreated oak and without any additives), As well as chimney sweeping powder (mixture of minerals).

Average burning time: between 1h30 and 2h30

Suitable for fireplaces, open fireplaces or

Closed, wood or coal stoves, boilers

With the log, a box of matches is included:

Sulfur-free safety matches per 100 from the 305 COCOONING Range

MIXED FSC certified matches N°C106867

Matches compliant with standard EN 1783:1997

Dangerous. Respect the precautions for use

Customs nomenclature: 44 01 39 00 00

Dimensions: 280 x 74 x 74 mm

Average weight: 1.2 kg

Gencode: 3 298 960 921 481



PCB - CARDBOARD

Characteristics: Ecu cardboard box without inscription

Capacity: 6 cases of chimney sweeping logs

Dimensions: 290 x 235 x 160 mm

Average weight: 7.4 kg

Gencode: 33 298 960 921 499



PALETTE

Packaging: 3 layers of 24 boxes, i.e. 72 boxes per pallet

EUROPE filmed (1200 x 800 mm), i.e. 432 cases in total

Stacking: Possible on 2 heights

Dimensions: 1200 x 800 x 1050 mm

Average net weight: 533 kg - Average gross weight: 555 kg

Gencode: 23 298 960 921 508



Non-contractual photo

FLAM'UP

Chemin du Paillard – CS 70 137 SAINTINES – 60 477 COMPIÈGNE CEDEX – France

Such. : +33 (0)3 44 38 76 00 – Fax: +33 (0)3 44 38 76 01

Web: www.flamup.fr - @: flamup@flamup.fr